

# DATA SHEET

Product: Pilot Plug AIS with 1.5m cable  
p/n: 100 1044

AIS Pilot Plug – housing with 4 mounting holes, ready made with 1.5 m cable; low smoke, halogen free

PIN	COLOUR/FARBE	SIGNAL
1	Brown/Braun	Tx - (out A)
4	White/Weiss	Tx + (out B)
5	Red/Rot	Rx - (in A)
6	Black/Schwarz	Rx + (in B)
9	Green/Grün	GND

**Note:** A pilot input/output port is part of an AIS Class A installation. A plug connected to this port should be installed on the bridge near the pilot's operating position, so that a pilot can connect a Personal Pilot Unit (PPU) if required. Also, a power connector for the pilot unit should be available nearby.

The pilot plug should be configured as follows (refer to SUB-COMMITTEE ON SAFETY OF NAVIGATION Circ. 227/6.1.2003):

<https://wwwcdn.imo.org/localresources/en/OurWork/Safety/Documents/AIS/SN.1-Circ.227.pdf>

## Cable Specification:

Environmental:	Indoor
Conductor:	5x 22 AWG (diameter: 0.75 mm)
Insulation:	PP – Polypropylene
Shield:	Aluminium/Polyester
Outer Jacket Material:	LSZH/FRNC
Cable diameter:	4.4 mm
Operating Temp:	-20°C to +70°C
RoHs :	compliant
ISO/IEC flammability :	IEC 60332-1
Amount of Halogen acc. To IEC 60754-1 and EN50267-1:	Zero

Revision: 2023/01